

(12) 按照专利合作条约所公布的国际申请

(19) 世界知识产权组织
国际局



(43) 国际公布日:
2004年9月30日(30.09.2004)

PCT

(10) 国际公布号:
WO 2004/084368 A1

(51) 国际分类号¹: H02B 7/06, H01F 27/10, 27/06, 27/38

(21) 国际申请号: PCT/CN2004/000076

(22) 国际申请日: 2004年1月20日(20.01.2004)

(25) 申请语言: 中文

(26) 公布语言: 中文

(30) 优先权:
03108110.X 2003年3月19日(19.03.2003) CN
03231909.6 2003年6月6日(06.06.2003) CN

(71) 申请人(对除美国以外的所有指定国): 上海科宏变电设备有限公司(SHANGHAI KEHONG ELECTRIC APPARATUS CO., LTD.) [CN/CN]; 中国上海市漕宝路103号5602室, Shanghai 200233 (CN)。

(72) 发明人: 及

(75) 发明人/申请人(仅对美国): 孙兵(SUN, Bing) [CN/CN]; 郑少俊(ZHENG, Shaojun) [CN/CN]; 刘爱和刘爱(LIU, Aihé) [CN/CN]; 中国上海市漕宝路103号上海科宏变电设备有限公司, Shanghai 200233 (CN)。

(74) 代理人: 隆天国际知识产权代理有限公司(LUNG TIN INTERNATIONAL INTELLECTUAL PROPERTY AGENT LTD.); 中国北京市朝阳区慧忠路5号远大中心B座18层, Beijing 100101 (CN)。

(81) 指定国(除另有指明, 要求每一种可提供的国家保护): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW

(84) 指定国(除另有指明, 要求每一种可提供的地区保护): ARIPO(BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), 欧亚专利(AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), 欧洲专利(AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

根据细则4.17的声明:

— 关于申请人在国际申请日有权申请并被授予专利(细则4.17(ii))对除美国以外的所有指定国


本国际公布:

— 包括国际检索报告。

所引用双字母代码和其它缩写符号, 请参考刊登在每期PCT公报期刊起始的“代码及缩写符号简要说明”。

(54) Title: A COMBINED TRANSFORMER AND PREFABRICATED SUBSTATIONS

(54) 发明名称: 组合式变压器和预装式变电站



A... THE LEVEL

(57) Abstract: A combined transformer is comprised of a transformer chamber, a low-voltage chamber, a high-voltage chamber and a radiator. There is a hollow thermal pipe filled with a heat-transfer medium in the radiator. One of the ends of the thermal pipe is plugged into the transformer chamber and on being located the other end there are heat sinks. Wherein the low-voltage chamber being located on the transformer and the high-voltage chamber being on the side of the transformer, the transformer chamber and the high-voltage chamber are embedded in the ground. The prefabricated substations are comprised of a transformer chamber, a transformer arranged in the transformer chamber, a switch chamber including a low-voltage chamber and a high-voltage chamber, a radiator and a hollow thermal pipe filled with a heat-transfer medium in the radiator. One of the ends of the thermal pipe is plugged into the transformer chamber and the other end is arranged thermally conductive sheets, the thermally conductive sheets are located on the outside of the switch chamber which is arranged on the transformer chamber. The high-voltage chamber and the low-voltage chamber both have doors the transformer chamber is enclosed with a pit and a cover. The said thermal pipe of the transformer dose not only has the large capacity, the long using life and high reliability, small size and the heat-transfer effect greatly improved but greatly reduces the occupation area of the transformer.

[见续页]



(57) 摘要

组合式变压器包括变压室，低压室，高压室，散热器，散热器上带有中空的热管，该热管空腔内充有传热介质，热管的一端插入变压室内，另一端设有散热片，低压室设置在变压室的上面，高压室设置在变压室的侧面，变压室和高压室埋入地下。预装式变电站包括变压室，安装在变压室內的变压器，其内设有低压室和高压室的开关室，散热器，散热器上带有中空的热管，该热管空腔内充有传热介质，热管的一端插入变压器内，另一端设有散热片，该散热片位于开关室的外侧面，开关室设置在变压室的上方，高压室和低压室设有门，变压室由地坑和盖板围成。上述变压器的热管的传热容量大，寿命长，可靠性高，体积小，散热效果大大改进，而且大大减小了变压器的占地面积。